

TWO WAY SOFT-CLOSE STANDARD EUROPEAN HINGES

TCH-11400 SERIES




Features

- Open angle 105°
- Double-actions operating type
- Soft-close built-in hydraulic damper
- Diameter of hinge cup 35mm
- Boring distance range 3mm to 7mm
- Height of hinge cup 11.5mm
- For door thickness 14mm to 21mm
- Compatible with existing mounting plates
- Finish: Nickel-plated



TCH-11407 F




Straight-arm

D	H	K	3	4	5	6	7
0	16	17	18	19	20		
3	13	14	15	16	17		
4	12	13	14	15	16		
5	11	12	13	14	15		

Abbreviations

H	mounting plate height
K	cup boring distance
D	door overlay

TCH-11407 H




Half-vented

D	H	K	3	4	5	6	7
0	7	8	9	10	11		
3	4	5	6	7	8		
4	3	4	5	6	7		
5	2	3	4	5	6		

Abbreviations

H	mounting plate height
K	cup boring distance
D	door overlay

TCH-11407 I




Full-vented

A	H	K	3	4	5	6	7
0	3	2	1				
3	6	5	4	3	2		
4	7	6	5	4	3		
5	8	7	6	5	4		

Abbreviations

H	mounting plate height
K	cup boring distance
A	reveal


Hinges per door




(Door width must not exceed 600 mm)

Application

Face frame cabinet Frameless cabinet



Cup centerpoint dimensions



Available mounting type

